

In the Claims:

1. (Currently Amended) A fuel cell apparatus system with a reformer and a mixture formation means, said mixture formation means comprising:

a fuel feed means;

an air feed means;

a mixture formation area, and

a fuel heating means,

wherein the fuel feed means includes a pressure impulse injection means,

wherein the mixture formation area is supplied with air and is positioned in line ~~behind~~

downstream of the fuel heating means ~~the pressure impulse injection means~~ and includes

a swirl chamber into which a nozzle connected to the pressure impulse injection means
~~device~~ discharges, and

wherein the fuel heating means is positioned in line ~~in front~~ downstream of the pressure
impulse injection means ~~injection device~~ for preheating the fuel to a temperature producing
spontaneous fuel vaporization at a nozzle outlet of said nozzle before injection.

2. (Currently Amended) The fuel cell apparatus system as claimed in claim 1, wherein
the pressure impulse injection means includes a changeover valve and the fuel heating means is
located in a fuel line located between the changeover valve and the nozzle.

3. (Currently Amended) The fuel cell apparatus system as claimed in claim 1, wherein
the fuel heating means heats the fuel to the temperature at which the vapor pressure of the fuel is
below a holding pressure determined by a pressure holding valve ~~of the pressure impulse~~
~~injection means.~~

4. (Currently Amended) The fuel cell apparatus system as claimed in claim 1, wherein
the air feed means includes an air heater.

5. (Currently Amended) The fuel cell apparatus ~~system~~ as claimed in claim 4, wherein the air heater heats the air to a temperature at which condensation of the fuel in the swirl chamber does not occur ~~no longer occurs~~.

6. (Currently Amended) The fuel cell apparatus ~~system~~ as claimed in claim 1, wherein the air feed supplies air continuously.